


### A classic terrazzo look with an endless colour palette













# Luster Effect












THE SWEET & SILKY MELODY OF COLORS



## **Technical Specification**



Kind Of Test	Test Method	Requirement As per IS 156222, Table 5, Group BIII, N≥ 20cm	e 5, Result	
deviation in length & width	IS 13630-1:2019	±0.2%	Avg 0.17 % / Avg 0.51mm	
deviation in thickness	IS 13630-1:2019	±5%	Avg -0.34 % / Avg -0.03mm	
deviation in straightness of sides	IS 13630-1:2019	±0.15%	Max ±0.08 % / Max ±0.25mm	
deviation in rectangularity	IS 13630-1:2019	±0.2%	Max ±0.09 % / Max ±0.28mm	
deviation in surface flatness	IS 13630-1:2019	±0.3%	Max 0.08 % / Max 0.33mm	
deviation in edge curvature	IS 13630-1:2019	±0.3%	Max 0.10 % / Max 0.29mm	
surface quality	IS 1363Q-1:2019	95% min	100%	



Kind Of Test	Test Method	Requirement	Result
scratch hardness of surface moh's scale	IS 13630-1:2019	3 moh's scale,min	3 moh's scale
water absorption	IS 13630-2:2019	Average >10%.	Average 14.78%
moisture expansion	IS 13630-3:2019	0.04 mm/m,max	0.034 mm/m
surface abrasion	IS 13630-11:2019	class II,min	class II ,600 rpm pass



Kind Of Test	Test Method	Requirement	Result	
breaking strength in N	IS 13630-6:2019	600 min for thickness ≥ 7.5 mm	average 635.19 N	
modulus of rupture (MOR)	IS 13630-6:2019	12 min for thickness ≥ 7.5 mm	average 15.03N/ mm²	
impact resistance ( COR)	IS 13630-14:2019	0.55, min	0.57	



#### Thermo photo characteristics

Kind Of Test	Test Method	Requirement	Result	
thermal shock resistance	IS 13630-5:2019	10 cycle,min	fully resistance	
coefficient of liner thermal expansion	IS 13630-4:2019	9X10 <sup>-</sup> 6 max	4.83x10 <sup>-</sup> 6	
crazing resistance	IS 13630-9:2019	4 cycle @ 7.5 bar, min	fully resistance	



Kind Of Test	Test Method	Requirement	Result
ain Resistance a) methylene blue 10g/I b) potassium permanganate	IS 13630-8:2019	class-1, min class-1, min	class 1
themical resistance house hold themical & swimming pool salt	IS 13630-8:2019	class AA min	GAA
hemical resistance low oncentrations acid & alkali ) hydrochloric acid solution 3% v/v ) citric acid soln. 100gm/L )potassium hydroxide soln. 200gm/L	IS 13630-8:2019	required, if agreed according to the chemical resistance class indicate by the manufacturer	GLAA GLAA GLAA

#### DOMESTIC PACKING DETAILS

Dimensions	Thickness	Pieces	Coverage Area		Box Weight
(mm)	(mm)	Per Box	(sqm.)	(sqft.)	(kg)
300x300	9.5	11	0.99	10.65	16 (approx)

#### NOTE:

- · Colours in the catalogue are as accurate as printing process allows. Please check actual tile sample before making the final selection.
- · Sizes mentioned in the catalogue are nominal sizes only.
- For better laying. Please follow the instructions on the packaging box.
- Please make sure to check the shade/finish with the sales agent/ dealer making the final purchase because there might be variation in actual finish that shown in the catalogue. The company will not bear any loss in such case.

## **PRODUCTS**



FLOOR TILES, WALL TILES, ELEVATION TILES, PARKING TILES, LABORATORY TILES, ROOF TILES, PEBBLE TILES, FULL BODY SLABS, QUARTZ SLAB & SPC FLOORING

GRANITES, MARBLES, SANDSTONES, ELEVATION STONES

TILES ADHESIVE & CHEMICALS,
FLOORING ACCESSORIES
MATERIALS

MODERN SANITARYWARE ELEGANT CP BATHROOM, KITCHEN FIXTURES & FITTINGS

